

BANSAL INSULATION AND MICA HOUSE

1763, Electrical Market, Bhagirath Palace, Chandni Chowk, Delhi – 110006, India

9013164104, 011-23876805, 9811068915

www.bansalinsulation.com ; bansal_insulations@yahoo.in

We deal in all kinds of Electrical Insulation, Transformer accessories and Safety products.

Resin Glass Tape Data Sheet

Specifications

• Thermal Class	• H
• Thermal Rating of Banding	• 200°C Max
• Yarn Used	• E Glass-75 1/2 or equivalent
• Thickness of Ends	• 0.3 mm approx
• Width tolerance	• ±10%
• No of Yarns	• 30 ±1/cm
• Weight per width	• 0.56 kg approx
• Tensile Strength B-Stage	• ≥ 2000 N/cm
• Tensile Strength C-Stage	• ≥ 2500 N/cm
• Resin Content	• Available from 24% to 30% as per customer requirement
• Curing Cycle	• 5hrs at 150 ° C, Once the job reaches the temp
• Arc Resistance(ASTM D 495)	• ≥ 120 sec.

Product Offer :

• Width Option	• 20mm, 25mm, 40mm, 50mm
• Length per roll options	• 200mtr, 100mtr
• Thermal Class options	• Class H-200°C, 220°C